

Slika	Artikel	Naziv	Teža, kg	Prostornina škatle, m ³	Število izdelkov, kos.	Bruto teža, kg	Opcije	Tabela velikosti																		
	CV-150	Kovinski aksialni kanalski ventilator D150	1,3	0,005	1	1,3		<table border="1"> <thead> <tr> <th>Model</th> <th>CV-150</th> <th>CV-160</th> <th>CV-200</th> <th>CV-250</th> <th>CV-300</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>200</td> <td>200</td> <td>220</td> <td>275</td> <td>315</td> </tr> <tr> <td>d</td> <td>150</td> <td>160</td> <td>200</td> <td>250</td> <td>300</td> </tr> </tbody> </table>	Model	CV-150	CV-160	CV-200	CV-250	CV-300	A	200	200	220	275	315	d	150	160	200	250	300
	Model	CV-150	CV-160	CV-200	CV-250	CV-300																				
	A	200	200	220	275	315																				
	d	150	160	200	250	300																				
	CV-160	Kovinski aksialni kanalski ventilator D160	1,3	0,005	1	1,3																				
CV-200	Kovinski aksialni kanalski ventilator D200	1,57	0,009	1	1,57																					
CV-250	Kovinski aksialni kanalski ventilator D250	2,78	0,02	1	2,78																					
CV-300	Kovinski aksialni kanalski ventilator D300	3,2	0,029	1	3,2																					

Karakteristike	Produktivnost (m ³ /h)	Raven hrupa, dB	Pritisk, Pa
CV-150	265	48	310
CV-160	370	48	310
CV-200	630	50	380
CV-250	680	50	400
CV-300	900	51	540



Loputa za preprečevanje povratnega ognja za aksialne gospodinske ventilatorje serije ERA (razen ERA 6), STANDARD, AURA, SLIM, COMFORT, FAVORITE, E, NEO, SILENT

	100 OK	Loputa za preprečevanje povratnega ognja D100	0,015	0,019	100	2	<table border="1"> <thead> <tr> <th>Model</th> <th>100 OK</th> <th>125 OK</th> <th>150 OK</th> </tr> </thead> <tbody> <tr> <td>D</td> <td>100</td> <td>125</td> <td>150</td> </tr> <tr> <td>B</td> <td>10,5</td> <td>12</td> <td>13,5</td> </tr> <tr> <td>A</td> <td>7</td> <td>8,5</td> <td>10</td> </tr> </tbody> </table>	Model	100 OK	125 OK	150 OK	D	100	125	150	B	10,5	12	13,5	A	7	8,5	10
	Model	100 OK	125 OK	150 OK																			
	D	100	125	150																			
B	10,5	12	13,5																				
A	7	8,5	10																				
125 OK	Loputa za preprečevanje povratnega ognja D125	0,024	0,019	75	2,2																		
150 OK	Loputa za preprečevanje povratnega ognja D150	0,038	0,019	40	1,8																		



KOMERCIALNI VENTILATORJI

Slika	Artikel	Naziv	Teža, kg	Prostornina škatle, m ³	Število izdelkov, kos.	Bruto teža, kg	Opcije	Tabela velikosti									
	STELS 125	Centrifugalni kanalski ventilator za dovod in odvod zraka D125 (jeklo)	4,8	0,128	4	19,7		<table border="1"> <thead> <tr> <th>Model</th> <th>STELS 125</th> <th>STELS 150</th> </tr> </thead> <tbody> <tr> <td>d</td> <td>125</td> <td>150</td> </tr> <tr> <td>E</td> <td>152</td> <td>172</td> </tr> </tbody> </table>	Model	STELS 125	STELS 150	d	125	150	E	152	172
	Model	STELS 125	STELS 150														
d	125	150															
E	152	172															
STELS 150	Centrifugalni kanalski ventilator za dovod in odvod zraka D150 (jeklo)	5	0,14	4	20,5												

Karakteristike	Produktivnost (m ³ /h)	Raven hrupa, dB	Pritisk, Pa
STELS 125	270	50	271
STELS 150	432	58	360